

Milwaukee 2854-20

M18 FUEL™ 3/8" Compact Impact Wrench w/ Friction Ring (Tool Only)

Item Number: MI-285420



Our M18 FUEL™ 3/8" Compact Impact Wrench w/ Friction Ring is the most compact in its class, delivering you the most access in tight spaces, up to 250 ft-lbs of nut-busting torque, and maximum workspace visibility. This battery-powered impact wrench measures only 4.8" in length with a POWERSTATE™ Brushless motor to provide the power to remove stubborn fasteners, even in confined spaces. The MILWAUKEE® 3/8" Compact Impact Wrench has tri-LEDs that surround the anvil to deliver you brighter light with fewer shadows. 4-Mode DRIVE CONTROL™ offers greater precision with a range of pre-set RPM and IPM levels, selectable from a single button on the tool. By selecting Mode 4, AUTO SHUT-OFF™ control applies no more than 20 ft-lbs of torque for hand-tight fastening applications to prevent overtightening. Mode 4 also features Bolt Removal Control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops. REDLINK PLUS™ Intelligence electronics make these controls possible while ensuring maximum performance, protecting the tool against overloads, over-heating, and over-discharge. The M18™ REDLITHIUM™ battery pack (not included) fits M18™ tools, delivering more work per charge and more work over the life of the pack.

Features

- Friction ring (hog ring) ensures quick and easy socket changes
- Compact length provides most access in tight spaces
- Powerstate™ brushless motor
- Tri-LEDs deliver high definition lighting to increase workspace visibility with less shadows
- 4-mode Drive Control™ provides greater control over output speed and power
- Auto Shut-Off™ control applies no more than 20 ft-lbs of torque for hand-tight fastening applications to prevent over-tightening
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- Redlink Plus™ Intelligence ensures maximum performance and protects from overloads, heating and over-discharge
- Works in up to 69kV environments
- Compatible with all M18™ batteries & chargers

Specifications

Fastening Torque	250 ft/lbs
Nut-Busting Torque	250 ft/lbs
IPM	0 - 3,500
RPM	0 - 2,400
Weight (LBS)	3.9
Warranty	5 Years